



YF-1700写真机



- 配置爱普生I3200原装喷头
EPSON I3200 Print head
- 高灵敏小车防撞装置
Anti-collision system
- 进口静音导轨及伺服一体电机
Imported mute rail and servo integrated motor
- 铝合金一体自动清洗墨栈
Big capacity bulk ink system
- 前中后三段材料加热设计
Three sections of material heating design: front, middle and rear
- 色彩艳丽,打印画面真实细腻
Bright colors, real and delicate printing pictures

机型/Model		YF-1700				
喷头 Printhead	爱普生I3200				固化系统 Curing System	热烘干+冷风风扇 Heating Dryer+Cooling Fan
喷头数量 Print Head number	1	2	3		输入格式 File Format	BMP/TIFF/EPS/PDF/AI/JPEG
色彩配置 Print Mode	C M Y K				RIP软件 RIP	Photoprint/Onyx/Caldera/色彩管理器 Photoprint/Onyx/Caldera/colorget
打印宽幅 Print Width	1600mm				数据传送接口 Data Connector	USB3.0
打印速度 Print Speed (sqm/h)	草图 3pass	29m ² /h	52m ² /h	73m ² /h	输入电源 Power	220VAC(±10%)单向, 50/60 HZ 220VAC(±10%) Single Phase, 50/60HZ
	标准 4pass	21m ² /h	39m ² /h	51m ² /h	机器功耗 Power Consumption	2600W
	高清 6pass	14m ² /h	25m ² /h	35m ² /h	机器尺寸/净重 Machine Size	2.5 m(L)*0.8 m(W)*1.2m(H)
打印分辨率 Print Resolution	720*1800 DPI				包装尺寸 Machine Size	2.75m(L)*0.78m(W)*0.75m(H)
打印材料 Media Type	车贴、灯箱布、网格布、PP、壁纸等 Vinly, Flex Banner, One Way Vision, PP Wall Paper				环境要求 Environment Requirement	独立、洁净、低尘、少光照、通风良好的 工作间环境温度: 20°C - 25°C, 相对湿度: 50% - 60% seperated, clean, low dust, well-ventilated, environmental temperature:20°C-25°C relative humidity:50%-60%
材料厚度 Media Thickness	材料厚度≤3mm Max. 3mm					
墨水类型 Ink Type	环保弱溶剂墨水/热升华墨水/水性墨水 ECO-Solvent ink/Sublimation ink Water-based ink					